

*AMENDMENTS TO THE CLAIMS*

This listing of claims replaces all prior versions, and listings, of claims in the application.

1. (Currently Amended) A pliers for cutting tubes comprising:

a first lever and a second lever articulated together on a pivot axis for pivoting between an open position for receiving a tube which is to be cut and a closed position after cutting of the tube, wherein

the second lever includes a blade,

the first lever includes

a rotary shaft parallel to the pivot axis of the first second levers,

and

a wheel rotatably mounted on ~~first lever~~ the rotary shaft and having a periphery including a plurality of grooves having respective, different widths for receiving tubes of different diameters so that a groove selected according to the diameter of a tube to be cut can be placed opposite the blade when the wheel is turned to a corresponding position.

2. (Currently Amended) The pliers according to Claim 1, wherein the blade has ~~two successive adjoining cutting edges between which a~~ intersecting at an outwardly projecting point is located.

Claim 3 (Cancelled).

4. (Currently Amended) The pliers according to Claim 1, ~~including a shaft mounted on the first lever,~~ wherein the wheel includes two disks that are parallel to one another ~~and,~~ mounted coaxially on the rotary shaft, and spaced from one another

on the rotary shaft, ~~the shaft being parallel to the pivot axis of the first and second levers.~~

5. (Currently Amended) The pliers according to Claim 4, wherein ~~each disk has the first lever includes two holes and each disk includes a plurality of pins in the same number as~~ projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, the pins cooperating with two the holes in the first lever to establish a respective stop position of the wheel each disk for each groove.

6. (Currently Amended) The pliers according to Claim 4, wherein the first lever has two branches between which ~~the wheel is~~ two disks are rotatably mounted,

each of the two branches terminates beyond the rotary shaft of the two disks, in a branch end including a hole, and

each disk includes pins ~~in the same number as~~ projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, each pin cooperating with a the respective hole in a the corresponding branch end to establish a respective stop position of the wheel each disk for a corresponding each groove.

7. (Currently Amended) The pliers according to Claim 4, ~~wherein~~ including a spring interposed between the two disks, relative to the rotary shaft, so that the disks mounted on the shaft can be tilted towards one another, against a return force of the spring, for releasing the pins from the holes for rotation of the disks around the rotary shaft.

Claims 8-10 (Cancelled).

11. (Currently Amended) The pliers according to Claim 5, ~~wherein~~ including a spring interposed between the two disks, relative to the rotary shaft, so that the disks mounted on the shaft can be tilted towards one another, against a return force of the spring, for releasing the pins from the holes for rotation of the disks around the rotary shaft.

12. (Currently Amended) The pliers according to Claim 6, ~~wherein~~ including a spring interposed between the two disks, relative to the rotary shaft, so that the disks mounted on the shaft can be tilted towards one another, against a return force of the spring, for releasing the pins from the holes for rotation of the disks around the rotary shaft.

Claim 13 (Cancelled).

14. (New) The pliers according to Claim 1, wherein the first lever includes a hole and the wheel includes a plurality of pins projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, the pins cooperating with the hole in the first lever to establish a respective stop position of the wheel for each groove.

15. (New) The pliers according to Claim 14, wherein the blade has two adjoining cutting edges intersecting at an outwardly projecting point.

16. (New) A pliers for cutting tubes comprising:

a first lever and a second lever articulated together on a pivot axis for pivoting between an open position for receiving a tube which is to be cut and a closed position after cutting of the tube, wherein

the second lever includes a blade,

the first lever includes

a rotary shaft, and  
a substantially planar wheel rotatably mounted on the rotary shaft and having a periphery including a plurality of grooves having respective, different widths for receiving tubes of different diameters so that a groove selected according to the diameter of a tube to be cut can be placed opposite the blade when the wheel is turned to a corresponding position.

17. (New) The pliers according to Claim 16, wherein the blade has two adjoining cutting edges intersecting at an outwardly projecting point.

18. (New) The pliers according to Claim 16, wherein the rotary shaft is parallel to the pivot axis of the first and second levers.

19. (New) The pliers according to Claim 16, wherein the first lever includes a hole and the wheel includes a plurality of pins projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, the pins cooperating with the hole in the first lever to establish a respective stop position of the wheel for each groove.

20. (New) A pliers for cutting tubes comprising:

a first lever and a second lever articulated together on a pivot axis for pivoting between an open position for receiving a tube which is to be cut and a closed position after cutting of the tube, wherein

the second lever includes a blade,

the first lever includes

a rotary shaft, and

two substantially planar disks rotatably and coaxially mounted on the rotary shaft and spaced from each other, each disk having a periphery including a plurality of grooves having respective, different widths for receiving tubes of different

diameters so that a groove selected according to the diameter of a tube to be cut can be placed opposite the blade when the disks are turned to a corresponding position.

21. (New) The pliers according to Claim 20, wherein the blade has two adjoining cutting edges intersecting at an outwardly projecting point.

22. (New) The pliers according to Claim 20, wherein the rotary shaft is parallel to the pivot axis of the first and second levers.

23. (New) The pliers according to Claim 20, wherein the first lever includes two holes and each disk includes a plurality of pins projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, the pins cooperating with the holes in the first lever to establish a respective stop position of each disk for each groove.

24. (New) The pliers according to Claim 20, wherein  
the first lever has two branches between which the two disks are rotatably mounted,  
each of the two branches terminates beyond the rotary shaft of the two disks, in a branch end including a hole, and  
each disk includes pins projecting parallel to the pivot axis of the first and second levers, each pin respectively corresponding to one of the grooves, each pin cooperating with the respective hole in the corresponding branch end to establish a respective stop position of each disk for each groove.

25. (New) The pliers according to Claim 24 including a spring interposed between the two disks, relative to the rotary shaft, so that the disks can be tilted towards one another, against a return force of the spring, for releasing the pins from the holes for rotation of the disks around the rotary shaft.